

DP



DP 40



DP 60

Pompe da drenaggio indicate per svuotamento di pozzi neri o cisterne, per giardinaggio; completamente in materiale anticorrosivo.

Drainage pump for emptying pits and cisterns, for gardening; completely constructed in anticorrosive material.

Bombas de drenaje indicadas para vaciar fosas sépticas o cisternas, para la jardinería; completamente de material anticorrosivo.

Pompes de drainage indiquées pour le vidage de fosses d'aisances ou citernes, pour le jardinage; entièrement en matériau anticorrosion.

CARATTERISTICHE COSTRUTTIVE / CONSTRUCTION FEATURES CARACTERÍSTICAS CONSTRUCTIVAS / CARACTÉRISTIQUES D'EXECUTION

Corpo pompa	polipropilene
Pump body	polypropylene
Cuerpo bomba	polipropileno
Corps de pompe	polypropylène
Girante	Noryl®
Impeller	
Rodete	
Turbine	
Tenuta meccanica	doppia tenuta a labbro
Mechanical seal	double lip seal
Sello mecánico	doble sello
Garniture mécanique	double joint d'étanchéité à lèvres
Albero motore	acciaio AISI 416 con boccia in ceramica
Motor shaft	stainless steel AISI 416 with ceramic bush
Eje motor	acero AISI 416 con casquillo de cerámica
Arbre moteur	acier AISI 416 avec bague en céramique
Passaggio corpi solidi	Ø max 4 mm
Passage of solids	
Paso de solidos	
Passage corps solides	
Profondità di immersione	max 5 m
Depth of immersion	
Profundidad inmersión	
Profondeur immersion	
Temperatura del liquido	0 - 40 °C
Liquid temperature	
Temperatura del liquido	
Température du liquide	
Cavo	H07 RNF, 10 m
Cable	
Cable	
Câble	
G	galleggiante
	float switch
	flotador
	flotteur

MOTORE / MOTOR / MOTOR / MOTEUR

Motore 2 poli a induzione	3~ 230/400V-50Hz
2 pole induction motor	1~ 230V-50Hz
Motor de 2 polos a inducción	con termoprotettore
Moteur à induction à 2 pôles	with thermal protection
	con protección térmica
	avec protection thermique
Classe di isolamento	F
Insulation class	
Clase de aislamiento	
Classe d'isolation	
Grado di protezione	IP68
Protection degree	
Grado de protección	
Protection	

Modelo	P2 motor (CV)	I (A) 1x230V	Caudal en lts/h								Código
			600	1500	3000	4000	4500	5000	6000	7000	
DP 60M	0,5	2.1	8,2	8	7,2	6,5	5,6	5	4	2,6	12463
DP 60MG											12464